



GNSS Firmware v7.1

Release Notes

September 2025

©Copyright Topcon Positioning Systems, Inc. 2025.

All contents in this document are copyrighted by Topcon. All rights reserved. The information contained herein may not be used, accessed, copied, stored, displayed, sold, modified, published, or distributed, or otherwise reproduced without express written consent from Topcon.

Table of Contents

SUPPORTED PRODUCTS 3

 SYSTEMS 3

SOFTWARE COMPATIBILITY 3

FEATURES AND CHANGES 3

Supported Products

Systems

- Topcon HiPer XR
- Sokkia GRX5

Software Compatibility

- GNSS FW v7.1 requires the following Topcon software versions (or later) to access all features and functionality:
 - TRU and SRU v4.1 (Note: TRU v4.0 is not compatible)
 - Pocket 3D v15.5.2 (Note: Pocket 3D v15.5.1 is not compatible)
 - Topcon Field and Office v10 (Note: Topcon Field and Office version 10 is only required for new feature support such as PPP and mmGPS)

Features and Changes

- New mmGPS functionality for precise millimeter accuracy. This feature requires an accessory cable for connection between the PZS-1 and HiPer XR. (P/N: 1065754-01)
- Skybridge/PPP corrections are now available through L-band or NTRIP
- Updated cybersecurity features
- Increased position measurements data rate to support 20 Hz
- Increased LongLink operational distance by at least 50%
- New Job Programming feature to schedule data collection
- Added start-up scripts
- Programmed wake-up time feature was added
- Added support for CMR message output with GPS and GLONASS corrections
- Added support for RTCM2 message output
- Updated Topcon Equipment Access Module (TEAM) option
- General improvements to stability, tracking, and positioning